








BLOCK OF THE MONTH SEWING MACHINE SEPTEMBER 2012



To create section A Cut one 3 1/4" x 1 1/2" sewing machine fabric
Cut two 1 1/2" x 1/1/2" background fabric


1. Sew background square to A rectangle, right side to right side as shown (stitch & flip method)
2. Press towards sewing machine fabric, trim backside
3. Repeat with other background square, press, trim backside



1/4" seam allowance
background indicated by shaded color
Completed block 9 1/2" x 6 1/2"

To create the spool

1. Sew C to B and repeat, press towards thead fabric
2. Sew D to CB, press towards D



Make one sewing machine block

To assemble the sewing machine block

1. Sew H to G, press towards G
2. Sew I to GH, press towards I
3. Sew J to GHI, press towards I
4. Sew K to A section, press towards A
5. Sew L to AK, press towards L
6. Sew M to AKL, press towards M
7. Sew N to AKLM, press towards N
8. Sew O to AKLMN, press towards N
9. Sew AKLMNO to GHIJ, press towards GHIJ
10. Sew P to AKLMNOGHIJ, press towards AKLMNOGHIJ
11. Sew E to spool, press towards spool
12. Sew F to other side of spool, press towards spool
13. Pin E, the spool and F to the sewing machine section, matching seam on right side of spool, press towards sewing machine.
14. Button optional

